



Military-Fasteners.com

P/N BACS12GM3-26

Description

Fastener Length: 1-5/8", Thread: 10-32, Thread Length: 1-17/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACS12GM326
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-539-1950
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACS12GM3-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.545 Inches Nominal
Fastener Length:	1.625 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.332 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw, Pointed, Full Thread
Screw Material:	Steel Comp 4130 Or Steel Comp 4340 Or Steel Comp 8740
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Ams Qq-p-416 Type Ii National Spec Single Treatment Response
Special Features:	Altered Item, Made From P/n Nas514p1032()p. Tapered Boss Machined On End, Min Angle Of 57 Degrees, Max Angle Of 63 Degrees, R3 Radius On Tip
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12GM3-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.