

**Description**

Fastener Length: 1-5/8", Thread: 10-32, Thread Length: 1-17/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	BACS12GM326
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-539-1950
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N BACS12GM3-26 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.545 Inches Nominal
<b>Fastener Length:</b>	1.625 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.332 Inches Nominal
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Screw, Pointed, Full Thread
<b>Screw Material:</b>	Steel Comp 4130 Or Steel Comp 4340 Or Steel Comp 8740
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Ams Qq-p-416 Type II National Spec Single Treatment Response
<b>Special Features:</b>	Altered Item, Made From P/n Nas514p1032( )p. Tapered Boss Machined On End, Min Angle Of 57 Degrees, Max Angle Of 63 Degrees, R3 Radius On Tip
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12GM3-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.