

P/N BACS12HN3K12

Description

Screw part number

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACS12HN3K12

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-596-7866

Schedule B: 7318.15.2010

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N BACS12HN3K12 Specifications

Fastener Length:	0.750 Inches Nominal
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	E-3 A/c
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nonmachine Nominal Thread Diameter:	0.190 Inches
Part Name Assigned By Controlling Agency:	Screw, Hex Head With Cross Recess, A286 Cres, 160 Ksi
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, T2, C3 Fed Spec Single Treatment Response Overall

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/BACS12HN3K12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/BACS12HN3K12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/BACS12HN3K12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/BACS12HN3K12 and selecting the quantity you want of the property of the