

**Description**

Screw part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACS12HN3K12
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-596-7866
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N BACS12HN3K12 Specifications

<b>Fastener Length:</b>	0.750 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.105 Inches Minimum And 0.120 Inches Maximum
<b>Width Between Flats:</b>	0.305 Inches Minimum And 0.314 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	E-3 A/c
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nonmachine Nominal Thread Diameter:</b>	0.190 Inches
<b>Part Name Assigned By Controlling Agency:</b>	Screw, Hex Head With Cross Recess, A286 Cres, 160 Ksi
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, T2, C3 Fed Spec Single Treatment Response Overall

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12HN3K12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.