

## P/N BACS12HW3AU9

### **Description**

Fastener Length: 27/32", Thread: 10-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACS12HW3AU9

Minimum Qty (MOQ): 15 EA

NSN: 5305-01-521-5116

Schedule B: 7318.15.2091

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# P/N BACS12HW3AU9 Specifications

Thursd Class	
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Minimum
Fastener Length:	0.823 Inches Minimum And 0.853 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Spline Minor Diameter:	0.110 Inches Minimum And 0.112 Inches Maximum
Spline Major Diameter:	0.154 Inches Minimum And 0.156 Inches Maximum
Locking Feature:	Prevailing Torque All Metal Design Overall
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Torx
End Item Identification:	Mv-22 Aircraft
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Thread Quantity Per Inch:	32
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Screw, Pan Head, Close Tolerance, Short Thread, Six Lobe
Special Features:	Underside Of Head, Root Of Threads And Thread Flanks 32 Microinches Ra. All Other Surfaces, 125 Microinches Ra.
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 A286 Assn Std Single Material Response Overall Or Ams5732 A286 Assn Std Single Material Response Overall Or Ams 5737 A286 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Ams-qq-p-35, Type Ii Or Viii Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/BACS12HW3AU9">https://military-fasteners.com/screws/machine+screws/BACS12HW3AU9</a> and selecting the quantity you want

