

Description

Fastener Length: 1-19/32", Thread: 10-32, Thread Length: 1/4", BACS12 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACS12HW3T21
Minimum Qty (MOQ):	1
NSN:	5305-01-538-6593
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N BACS12HW3T21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Nominal
Fastener Length:	1.573 Inches Minimum And 1.603 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Internal Drive Style:	Torx
End Item Identification:	Cv-22
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.302 Inches Minimum And 1.322 Inches Maximum
Thread Quantity Per Inch:	32
Part Name Assigned By Controlling Agency:	Screw,pan Head,close Tolerance
Special Features:	Lubricated With Cetyl Alcohol
Material:	Titanium Alloy Uns R56400 Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12HW3T21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.