

Description

Fastener Length: 7/16", Thread: 8-32, Thread Length: 9/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | BACS12N87 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-807-9075 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N BACS12N8-7 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.296 Inches Minimum |
| Fastener Length: | 0.406 Inches Minimum And 0.437 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.275 Inches Minimum And 0.305 Inches Maximum |
| Washer Quantity: | 1 |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 28.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall |
| Countersink Angle: | 100.0 Degrees Nominal |
| Primary Washer Outside Diameter: | 0.645 Inches Minimum And 0.665 Inches Maximum |
| Primary Washer Style: | Dome Internal Teeth |
| Primary Washer Material Thickness: | 0.017 Inches Nominal |
| Secondary Washer Material Thickness: | 0.017 Inches Nominal |
| Material: | Steel Comp 1022 Overall Or Steel Comp 1050 Overall |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12N8-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.