

Description

Fastener Length: 7/16", Thread: 8-32, Thread Length: 9/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACS12N87
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-807-9075
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACS12N8-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.296 Inches Minimum
Fastener Length:	0.406 Inches Minimum And 0.437 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.275 Inches Minimum And 0.305 Inches Maximum
Washer Quantity:	1
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	28.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Countersink Angle:	100.0 Degrees Nominal
Primary Washer Outside Diameter:	0.645 Inches Minimum And 0.665 Inches Maximum
Primary Washer Style:	Dome Internal Teeth
Primary Washer Material Thickness:	0.017 Inches Nominal
Secondary Washer Material Thickness:	0.017 Inches Nominal
Material:	Steel Comp 1022 Overall Or Steel Comp 1050 Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12N8-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.