



Military-Fasteners.com

P/N BACW10AU3

Description

Hole Diameter: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACW10AU3
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-083-9303
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N BACW10AU3 Specifications

Hole Diameter:	0.252 Inches Minimum And 0.258 Inches Maximum
Radius:	0.235 Inches Minimum And 0.240 Inches Maximum
Outside Diameter:	0.375 Inches Minimum And 0.385 Inches Maximum
Recess Depth:	0.040 Inches Minimum And 0.050 Inches Maximum
Material Thickness:	0.078 Inches Minimum And 0.088 Inches Maximum
Hardness Rating:	38.0 Rockwell C Minimum And 44.0 Rockwell C Maximum
Surface Finish:	63.0 Microinches Counterbore Wall
Heat Treatment:	As Fabricated
Material:	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 4130 Overall Or Steel Comp 4027 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall Or Mil-s-18729 Mil Spec 3rd Material Response Overall Or Astm A322 Assn Std 4th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Concave
Specification/standard Data:	81205-bacw10au Manufacturers Standard

How to Order

Order this tln washer from our inventory online by visiting <https://military-fasteners.com/washers/finishing+washers/BACW10AU3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.