

**Description**

hole diameter: 0.25", recessed,

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	BACW10BP4ACU
Minimum Qty (MOQ):	50
NSN:	5310-00-498-5605
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



## P/N BACW10BP4ACU Specifications

<b>Hole Diameter:</b>	0.250 Inches Minimum And 0.261 Inches Maximum
<b>Outside Diameter:</b>	0.475 Inches Minimum And 0.495 Inches Maximum
<b>Recess Diameter:</b>	0.332 Inches Minimum And 0.352 Inches Maximum
<b>Material Thickness:</b>	0.057 Inches Minimum And 0.069 Inches Maximum
<b>Minimum Tensile Strength:</b>	140000 Pounds Per Square Inch
<b>Recess Angle:</b>	90.0 Degrees Minimum And 100.0 Degrees Maximum
<b>Material:</b>	Steel Comp 301 Overall
<b>Material Document And Classification:</b>	Ams 5518 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	15 Recessed
<b>Style Designator:</b>	Recessed
<b>Specification/standard Data:</b>	81205-bacw10bp Manufacturers Standard

## How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/BACW10BP4ACU> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.