

Description

hole diameter: 0.25", recessed,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACW10BP4ACU
Minimum Qty (MOQ):	50
NSN:	5310-00-498-5605
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N BACW10BP4ACU Specifications

Hole Diameter:	0.250 Inches Minimum And 0.261 Inches Maximum
Outside Diameter:	0.475 Inches Minimum And 0.495 Inches Maximum
Recess Diameter:	0.332 Inches Minimum And 0.352 Inches Maximum
Material Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Recess Angle:	90.0 Degrees Minimum And 100.0 Degrees Maximum
Material:	Steel Comp 301 Overall
Material Document And Classification:	Ams 5518 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed
Style Designator:	Recessed
Specification/standard Data:	81205-bacw10bp Manufacturers Standard

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/BACW10BP4ACU> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.