

Description

Hole Diameter: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACW10BP5AC
Minimum Qty (MOQ):	50 EA
NSN:	5310-01-051-8100
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE
AVAILABLE

P/N BACW10BP5AC Specifications

Hole Diameter:	0.313 Inches Minimum And 0.324 Inches Maximum
Outside Diameter:	0.585 Inches Minimum And 0.605 Inches Maximum
Recess Diameter:	0.394 Inches Minimum And 0.414 Inches Maximum
Material Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Recess Angle:	90.0 Degrees Minimum And 100.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall
Surface Treatment Document And Classification:	Ams 2416 Assn Std Single Treatment Response Overall
Style Designator:	15 Recessed
Specification/standard Data:	81205-bacw10bp Manufacturers Standard

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/finishing+washers/BACW10BP5AC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.