

Description

BACW10BP6CD Recessed Washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | BACW10BP6CD |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-01-190-7578 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



* See page 2 for technical characteristics

P/N BACW10BP6CD Specifications

| | |
|---|---|
| Hole Diameter: | 0.376 Inches Minimum And 0.387 Inches Maximum |
| Outside Diameter: | 0.649 Inches Minimum And 0.669 Inches Maximum |
| Recess Diameter: | 0.489 Inches Minimum And 0.509 Inches Maximum |
| Material Thickness: | 0.057 Inches Minimum And 0.069 Inches Maximum |
| Minimum Tensile Strength: | 140000 Pounds Per Square Inch |
| Recess Angle: | 90.0 Degrees Minimum And 100.0 Degrees Maximum |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5525 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 15 Recessed |
| Specification/standard Data: | 81205-bacw10bp Manufacturers Standard |

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/BACW10BP6CD> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.