

Description

Fastener Length: 7/16", Thread: 5-40, Thread Length: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | BB30262 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-00-034-5230 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N BB302-6-2 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.304 Inches Nominal |
| Fastener Length: | 0.419 Inches Minimum And 0.439 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.247 Inches Minimum And 0.251 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.125 Inches |
| Thread Quantity Per Inch: | 40 |
| Countersink Angle: | 100.0 Degrees Nominal |
| Screw Material: | Steel Comp 431 |
| Screw Material Document And Classification: | Qq-s-763 Fed Spec Single Material Response |
| Thread Series Designator: | Unc |

How to Order

Order this blindbolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BB302-6-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.