

Description

Fastener Length: 19/32", Thread Size: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BB30283
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-057-3194
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BB302-8-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.579 Inches Minimum And 0.599 Inches Maximum
Head Style:	Dished Countersunk
Shank Diameter:	0.163 Inches Minimum And 0.165 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.3304 Inches Maximum
Grip Length:	0.188 Inches Nominal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Shear Strength:	125000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 431 Overall
Material Document And Classification:	Aisi Assn Std Single Material Response Overall
Thread Series Designator:	Unjc

How to Order

Order this blindbolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BB302-8-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.