

Description

Fastener Length: 19/32", Thread Size: 5/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BB30283
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-057-3194
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N BB302-8-3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.579 Inches Minimum And 0.599 Inches Maximum
<b>Head Style:</b>	Dished Countersunk
<b>Shank Diameter:</b>	0.163 Inches Minimum And 0.165 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.3304 Inches Maximum
<b>Grip Length:</b>	0.188 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Shear Strength:</b>	125000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Comp 431 Overall
<b>Material Document And Classification:</b>	Aisi Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this blindbolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BB302-8-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.