

Description

Fastener Length: 25/32", Thread: 8-32, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BB30286
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-105-6911
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N BB302-8-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.381 Inches Minimum And 0.421 Inches Maximum
Fastener Length:	0.766 Inches Minimum And 0.786 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.325 Inches Minimum And 0.330 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel Comp 431
Screw Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response
Thread Series Designator:	Unc

How to Order

Order this blindbolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BB302-8-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.