

Description

BLNS series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BLNS410
Minimum Qty (MOQ):	1
NSN:	5315-00-422-1716
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N BLNS4-10 Specifications

Shank Diameter:	0.245 Inches Minimum And 0.248 Inches Maximum
Ring Handle Diameter:	1.187 Inches Maximum
Detent Quantity:	2
Grip Length:	1.000 Inches Minimum And 1.020 Inches Maximum
Actuation Type:	Pull And Push
Shear Strength:	8500 Double Pounds Per Square Inch
Detent To Tapered End Distance:	0.344 Inches Maximum
Material:	Steel Comp 4130 Shank
Material:	Steel Comp 440c Detent
Material:	Steel Ring
Material:	Steel Spring
Material Document And Classification:	Mil-s-6758,sae 4130 Mil Spec Single Material Response Shank
Material Document And Classification:	Qq-s-763,class 440c Fed Spec Single Material Response Detent
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ring
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Spring
Surface Treatment:	Cadmium Ring
Surface Treatment:	Cadmium Shank
Surface Treatment:	Cadmium Spring
Surface Treatment Document And Classification:	Qq-p-416,type 1,class 3 Or Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Ring
Surface Treatment Document And Classification:	Qq-p-416,type 1,class 3 Or Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Shank
Surface Treatment Document And Classification:	Qq-p-416,type 1,class 3 Or Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Spring
Style Designator:	Ring Handle

How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/BLNS4-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.