

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	C10001AD58
Minimum Qty (MOQ):	200 EA
NSN:	5320-01-398-9465
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N C10001AD5-8 Specifications

Fastener Length:	0.485 Inches Minimum And 0.520 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Height:	0.045 Inches Minimum And 0.051 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.326 Inches Minimum And 0.344 Inches Maximum
End Item Identification:	W/s: Aircraft, F-16
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Specification/standard Data:	81755-c10001 Manufacturers Specification Control

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/C10001AD5-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.