

**Description**

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	C10001AD59
Minimum Qty (MOQ):	85 EA
NSN:	5320-01-398-8735
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N C10001AD5-9 Specifications

<b>Fastener Length:</b>	0.547 Inches Minimum And 0.582 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Height:</b>	0.045 Inches Minimum And 0.051 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.326 Inches Minimum And 0.344 Inches Maximum
<b>End Item Identification:</b>	W/s: Aircraft, F-16
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Specification/standard Data:</b>	81755-c10001 Manufacturers Specification Control

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/C10001AD5-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.