

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	C10001AD610
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-398-8736
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N C10001AD6-10 Specifications

Fastener Length:	0.610 Inches Minimum And 0.645 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Height:	0.058 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.187 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.388 Inches Minimum And 0.406 Inches Maximum
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-q-430 Fed Spec Single Material Response Overall
Specification/standard Data:	81755-c10001 Manufacturers Specification Control

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/C10001AD6-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.