

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	C10001AD66
Minimum Qty (MOQ):	130 EA
NSN:	5320-01-398-8737
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N C10001AD6-6 Specifications

Fastener Length:	0.360 Inches Minimum And 0.395 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Height:	0.058 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.187 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.388 Inches Minimum And 0.406 Inches Maximum
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Specification/standard Data:	81755-c10001 Manufacturers Specification Control

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/C10001AD6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.