

**Description**

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	C10001AD69
Minimum Qty (MOQ):	95 EA
NSN:	5320-01-398-9498
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N C10001AD6-9 Specifications

<b>Fastener Length:</b>	0.547 Inches Minimum And 0.582 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Height:</b>	0.058 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.187 Inches Minimum And 0.191 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.388 Inches Minimum And 0.406 Inches Maximum
<b>End Item Identification:</b>	W/s: Aircraft, F-16
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Specification/standard Data:</b>	81755-c10001 Manufacturers Specification Control

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/C10001AD6-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.