

Description

Diameter: 13/64", plastic polytetrafluoroethylene cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|------------------------------------|
| SKU / Model: | C2874D4 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-00-837-4103 |
| Schedule B: | 7616.10.1000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |

NO IMAGE
AVAILABLE

P/N C2874D4 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Any Acceptable |
| Overall Width: | 0.375 Inches Nominal |
| Diameter: | 0.201 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.029 Inches Minimum And 0.035 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 0.457 Inches Nominal |
| Distance From Loop Center To Tongue End: | 0.645 Inches Nominal |
| Loop Inside Diameter: | 0.235 Inches Minimum And 0.265 Inches Maximum |
| Material: | Aluminum Alloy 2024 Band |
| Material: | Plastic Polytetrafluoroethylene Cushion |
| Material Document And Classification: | Qq-a-250/5,t4 Fed Spec Single Material Response Band |
| Surface Treatment: | Anodize Band |
| Style Designator: | Offset Mount |

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/C2874D4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.