



Military-Fasteners.com

P/N C305-4-17

Description

Fastener Length: 1-19/32", Thread: 1/4-28, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	C305417
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-040-4695
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N C305-4-17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.506 Inches Minimum And 0.556 Inches Maximum
Fastener Length:	1.578 Inches Minimum And 1.608 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.254 Inches Nominal
Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.465 Inches Minimum And 0.475 Inches Maximum
Extended Washer Thickness:	0.042 Inches Nominal
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.052 Inches Minimum And 1.072 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	260000 Pounds Per Square Inch
Hardness Rating:	51.0 Rockwell C Minimum Overall And 54.0 Rockwell C Maximum Overall
Material:	Steel Comp H11 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C305-4-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.