

Description

Fastener Length: 1-19/32", Hole Diameter: ", Thread: 3/8-24, Thread Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	C3056H14
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-182-9358
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N C305-6H14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.682 Inches Minimum And 0.732 Inches Maximum
Fastener Length:	1.567 Inches Minimum And 1.597 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.405 Inches Nominal
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Extended Washer Diameter:	0.715 Inches Minimum And 0.725 Inches Maximum
Extended Washer Thickness:	0.075 Inches Nominal
Hole Diameter:	0.055 Inches Nominal
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	260000 Pounds Per Square Inch
Hardness Rating:	51.0 Rockwell C Minimum Overall And 54.0 Rockwell C Maximum Overall
Hole Configuration Style:	Round Longitudinal Hole
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6485 Assn Std Single Material Response Overall Or Ams6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Mil-c-8837,ty 1,cl 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C305-6H14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.