

Description

Fastener Length: 1-63/64", Thread: 3/8-20, Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	C305719
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-466-0476
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N C305-7-19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.789 Inches Minimum And 0.839 Inches Maximum
Fastener Length:	1.986 Inches Minimum And 2.016 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.464 Inches Nominal
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Extended Washer Diameter:	0.820 Inches Minimum And 0.830 Inches Maximum
Extended Washer Thickness:	0.083 Inches Nominal
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Nominal Thread Diameter:	0.437 Inches
Grip Length:	1.177 Inches Minimum And 1.197 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	260000 Pounds Per Square Inch
Hardness Rating:	51.0 Rockwell C Minimum Overall And 62.0 Rockwell C Maximum Overall
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6485 Assn Std Single Material Response Overall Or Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Mil-c-8837 Ty 1 Class 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C305-7-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.