

**Description**

Fastener Length: 1-63/64", Thread: 3/8-20, Thread Length: 53/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	C305719
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-466-0476
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N C305-7-19 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.789 Inches Minimum And 0.839 Inches Maximum
<b>Fastener Length:</b>	1.986 Inches Minimum And 2.016 Inches Maximum
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.464 Inches Nominal
<b>Width Between Flats:</b>	0.553 Inches Minimum And 0.564 Inches Maximum
<b>Extended Washer Diameter:</b>	0.820 Inches Minimum And 0.830 Inches Maximum
<b>Extended Washer Thickness:</b>	0.083 Inches Nominal
<b>Grip Diameter:</b>	0.4360 Inches Minimum And 0.4370 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.437 Inches
<b>Grip Length:</b>	1.177 Inches Minimum And 1.197 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	260000 Pounds Per Square Inch
<b>Hardness Rating:</b>	51.0 Rockwell C Minimum Overall And 62.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp H11 Overall
<b>Material Document And Classification:</b>	Ams 6485 Assn Std Single Material Response Overall Or Ams 6487 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-8837 Ty 1 Class 2 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C305-7-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.