

Description

Fastener Length: 57/64", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	C752139
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-050-4988
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N C7521-3-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.871 Inches Minimum And 0.891 Inches Maximum
Head Style:	Spline Drive Shear Head
Head Height:	0.140 Inches Nominal
Grip Diameter:	0.1885 Inches Minimum And 0.1894 Inches Maximum
Single Shear Strength:	132000 Pounds Per Square Inch
Head Minor Diameter:	0.456 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.548 Inches Minimum And 0.568 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C7521-3-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.