

**Description**

Fastener Length: 57/64", Thread: 10-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | C752139                                   |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-050-4988                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N C7521-3-9 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.323 Inches Nominal                               |
| <b>Fastener Length:</b>                               | 0.871 Inches Minimum And 0.891 Inches Maximum      |
| <b>Head Style:</b>                                    | Spline Drive Shear Head                            |
| <b>Head Height:</b>                                   | 0.140 Inches Nominal                               |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1894 Inches Maximum    |
| <b>Single Shear Strength:</b>                         | 132000 Pounds Per Square Inch                      |
| <b>Head Minor Diameter:</b>                           | 0.456 Inches Nominal                               |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches                                       |
| <b>Grip Length:</b>                                   | 0.548 Inches Minimum And 0.568 Inches Maximum      |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 220000 Pounds Per Square Inch                      |
| <b>Material:</b>                                      | Steel Overall                                      |
| <b>Material Document And Classification:</b>          | Ams 6487 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall                                    |
| <b>Surface Treatment Document And Classification:</b> | Nas 672 Assn Std Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C7521-3-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.