



Military-Fasteners.com

P/N C7521-5-10

Description

Fastener Length: 1-1/16", Thread: 1/4-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | C7521510 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-054-3409 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N C7521-5-10 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Nominal |
| Fastener Length: | 1.053 Inches Minimum And 1.073 Inches Maximum |
| Head Style: | Spline Drive Shear Head |
| Head Height: | 0.187 Inches Nominal |
| Grip Diameter: | 0.3108 Inches Minimum And 0.3117 Inches Maximum |
| Single Shear Strength: | 132000 Pounds Per Square Inch |
| Head Minor Diameter: | 0.605 Inches Nominal |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Material Document And Classification: | Ams 6487 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Nas 672 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C7521-5-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.