



Military-Fasteners.com

P/N C7521-5-10

Description

Fastener Length: 1-1/16", Thread: 1/4-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	C7521510
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-054-3409
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N C7521-5-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	1.053 Inches Minimum And 1.073 Inches Maximum
Head Style:	Spline Drive Shear Head
Head Height:	0.187 Inches Nominal
Grip Diameter:	0.3108 Inches Minimum And 0.3117 Inches Maximum
Single Shear Strength:	132000 Pounds Per Square Inch
Head Minor Diameter:	0.605 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C7521-5-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.