

Description

Fastener Length: 2-55/64", Thread: 3/8-24, Thread Length: 39/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	C7984636
Minimum Qty (MOQ):	1
NSN:	5305-01-107-0036
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N C7984-6-36 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.569 Inches Minimum And 0.619 Inches Maximum
Fastener Length:	2.829 Inches Minimum And 2.859 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.515 Inches Minimum And 0.566 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.240 Inches Minimum And 2.260 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 49.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C7984-6-36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.