

**Description**

Fastener Length: 1-21/64", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | C7984B316                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-298-1300                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N C7984B3-16 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.298 Inches Minimum And 0.348 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 1.308 Inches Minimum And 1.338 Inches Maximum                       |
| <b>Head Style:</b>                                    | Flat Countersunk  |
| <b>Head Diameter:</b>                                 | 0.325 Inches Minimum And 0.385 Inches Maximum                       |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum                     |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                                       |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 0.990 Inches Minimum And 1.010 Inches Maximum                       |
| <b>Features Provided:</b>                             | Dry Film Lubricant  |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 220000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                      |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head                            |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads  |
| <b>Material:</b>                                      | Steel Comp H11 Overall  |
| <b>Material Document And Classification:</b>          | Ams 6487 Assn Std Single Material Response Overall                  |
| <b>Surface Treatment:</b>                             | Aluminum Overall And Chromate Overall                               |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall    |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/C7984B3-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.