

Description

Fastener Length: 11/16", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	C798535
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-054-6260
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N C7985-3-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Minimum And 0.388 Inches Maximum
Fastener Length:	0.660 Inches Minimum And 0.690 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.258 Inches Minimum And 0.305 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 49.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C7985-3-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.