

**Description**

Fastener Length: 27/32", Thread: 1/4-28, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	C798547R
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-428-2139
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N C7985-4-7R Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.332 Inches Minimum And 0.403 Inches Maximum
<b>Fastener Length:</b>	0.826 Inches Minimum And 0.856 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.350 Inches Minimum And 0.399 Inches Maximum
<b>Shoulder Diameter:</b>	0.2637 Inches Minimum First Shoulder And 0.2643 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.428 Inches Minimum First Shoulder And 0.448 Inches Maximum First Shoulder
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	220000 Pounds Per Square Inch
<b>Hardness Rating:</b>	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	132000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Nominal And 101.0 Degrees Maximum
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Steel Comp H11 Overall
<b>Material Document And Classification:</b>	Ams 6487 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Nas 672 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C7985-4-7R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.