

Description

Fastener Length: 3-1/4", Thread: 5/8-18, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	C79861052
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-056-4220
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N C7986-10-52 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.990 Inches Minimum And 1.020 Inches Maximum
Fastener Length:	3.250 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	1.201 Inches Minimum And 1.272 Inches Maximum
Grip Diameter:	0.6230 Inches Minimum And 0.6240 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.625 Inches
Grip Length:	2.235 Inches Minimum And 2.255 Inches Maximum
Thread Quantity Per Inch:	18
Hardness Rating:	46.0 Rockwell C Minimum Overall And 49.0 Rockwell C Maximum Overall
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/C7986-10-52> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.