

**Description**

Fastener Length: 1-3/8", Thread: 3/8-24, Thread Length: 37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | C9535613                                  |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-054-6233                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N C9535-6-13 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.555 Inches Minimum And 0.585 Inches Maximum   |
| <b>Fastener Length:</b>                               | 1.382 Inches Nominal  |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.515 Inches Minimum And 0.535 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.096 Inches Minimum And 0.106 Inches Maximum   |
| <b>Grip Diameter:</b>                                 | 0.3735 Inches Minimum And 0.3745 Inches Maximum   |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)   |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches  |
| <b>Grip Length:</b>                                   | 0.802 Inches Minimum And 0.822 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 220000 Pounds Per Square Inch   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads  |
| <b>Special Features:</b>                              | Conical Bearing Surface Of Head 99.0 Degree To 101.0 Degree Included Angle 0.065 In. Long |
| <b>Material:</b>                                      | Steel Comp H11 Overall  |
| <b>Material Document And Classification:</b>          | Ams 6487 Assn Std Single Material Response Overall  |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Nas 672 Assn Std Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C9535-6-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.