

Description

Fastener Length: 1-3/8", Thread: 3/8-24, Thread Length: 37/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	C9535613
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-054-6233
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N C9535-6-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.555 Inches Minimum And 0.585 Inches Maximum
Fastener Length:	1.382 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.515 Inches Minimum And 0.535 Inches Maximum
Head Height:	0.096 Inches Minimum And 0.106 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Conical Bearing Surface Of Head 99.0 Degree To 101.0 Degree Included Angle 0.065 In. Long
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C9535-6-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.