

**Description**

Fastener Length: 1-15/16", Thread: 3/8-24, Thread Length: 37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | C9535622                                  |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5305-01-239-2407                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N C9535-6-22 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.555 Inches Minimum And 0.585 Inches Maximum     |
| <b>Fastener Length:</b>                               | 1.945 Inches Nominal                              |
| <b>Head Style:</b>                                    | Flush   |
| <b>Head Diameter:</b>                                 | 0.515 Inches Minimum And 0.535 Inches Maximum     |
| <b>Head Height:</b>                                   | 0.167 Inches Nominal                              |
| <b>Grip Diameter:</b>                                 | 0.3735 Inches Minimum And 0.3745 Inches Maximum   |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                     |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches                                      |
| <b>Grip Length:</b>                                   | 1.365 Inches Minimum And 1.385 Inches Maximum     |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 220000 Pounds Per Square Inch                     |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head          |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip                             |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                          |
| <b>Material:</b>                                      | Steel Comp H11 Overall                            |
| <b>Material Document And Classification:</b>          | Ams6487 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall                                   |
| <b>Surface Treatment Document And Classification:</b> | Nas672 Assn Std Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C9535-6-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.