

Description

Fastener Length: 2-13/64", Thread: 3/8-24, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | C9535626 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-236-6191 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N C9535-6-26 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.545 Inches Minimum And 0.595 Inches Maximum |
| Fastener Length: | 2.180 Inches Minimum And 2.210 Inches Maximum |
| Head Style: | Fillister Countersunk |
| Head Diameter: | 0.515 Inches Minimum And 0.535 Inches Maximum |
| Head Height: | 0.096 Inches Minimum And 0.109 Inches Maximum |
| Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 1.615 Inches Minimum And 1.635 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Special Features: | Top Of Head Is Flat |
| Material: | Steel Comp H11 Overall |
| Material Document And Classification: | Ams 6487 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C9535-6-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.