

P/N C9535-7-16

Description

Fastener Length: 1-11/16", Thread: 7/16-20, Thread Length: 43/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: C9535716

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-054-6246

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N C9535-7-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.668 Inches Minimum And 0.698 Inches Maximum
Fastener Length:	1.683 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.605 Inches Minimum And 0.625 Inches Maximum
Head Height:	0.112 Inches Minimum And 0.125 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.438 Inches
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Conical Bearing Surface Of Head 99.0 Degree To 101.0 Degree Included Angle 0.077 In. Long
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/C9535-7-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.