



Military-Fasteners.com

P/N C9535-7-19

Description

Fastener Length: 1-7/8", Thread: 3/8-20, Thread Length: 45/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	C9535719
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-236-6192
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N C9535-7-19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.658 Inches Minimum And 0.708 Inches Maximum
Fastener Length:	1.856 Inches Minimum And 1.886 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.605 Inches Minimum And 0.625 Inches Maximum
Head Height:	0.112 Inches Minimum And 0.125 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.437 Inches
Grip Length:	1.178 Inches Minimum And 1.198 Inches Maximum
Thread Quantity Per Inch:	20
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Top Of Head Is Flat
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C9535-7-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.