

P/N C9535-7-21

Description

Fastener Length: 1-", Thread: 7/16-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: C9535721

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-054-4624

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N C9535-7-21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.668 Inches Minimum And 0.698 Inches Maximum
Fastener Length:	1.995 Inches Nominal
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.438 Inches
Grip Length:	1.302 Inches Minimum And 1.322 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/C9535-7-21 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/C9535-7-21 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/C9535-7-21 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/C9535-7-21 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/c9535-7-21 and selecting the quantity you want then cart in the property of the property of