

Description

Fastener Length: 2-5/16", Thread: 7/16-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | C9535726 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-288-5723 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N C9535-7-26 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.668 Inches Minimum And 0.698 Inches Maximum |
| Fastener Length: | 2.270 Inches Minimum And 2.320 Inches Maximum |
| Head Style: | Flush |
| Head Diameter: | 0.615 Inches Minimum And 0.898 Inches Maximum |
| Head Height: | 0.195 Inches Nominal |
| Grip Diameter: | 0.4360 Inches Minimum And 0.4370 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.438 Inches |
| Grip Length: | 1.602 Inches Minimum And 1.622 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp H11 Overall |
| Material Document And Classification: | Ams 6487 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C9535-7-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.