

P/N C9535-7-26

Description

Fastener Length: 2-5/16", Thread: 7/16-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: C9535726
Minimum Qty (MOQ): 5 EA

NSN: 5305-01-288-5723

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N C9535-7-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.668 Inches Minimum And 0.698 Inches Maximum
Fastener Length:	2.270 Inches Minimum And 2.320 Inches Maximum
Head Style:	Flush
Head Diameter:	0.615 Inches Minimum And 0.898 Inches Maximum
Head Height:	0.195 Inches Nominal
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.438 Inches
Grip Length:	1.602 Inches Minimum And 1.622 Inches Maximum
Thread Quantity Per Inch:	20
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/C9535-7-26 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.