

Description

Fastener Length: 2-53/64", Thread: 7/16-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	C9535734
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-191-3126
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N C9535-7-34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.668 Inches Minimum And 0.698 Inches Maximum
Fastener Length:	2.783 Inches Minimum And 2.833 Inches Maximum
Head Style:	Flush
Head Diameter:	0.605 Inches Minimum And 0.625 Inches Maximum
Head Height:	0.195 Inches Nominal
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.438 Inches
Grip Length:	2.115 Inches Minimum And 2.135 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C9535-7-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.