

**Description**

Fastener Length: 3-", Thread: 7/16-20, Thread Length: 11/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	C9535739
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-054-6251
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N C9535-7-39 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.668 Inches Minimum And 0.698 Inches Maximum
<b>Fastener Length:</b>	3.121 Inches Nominal
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.605 Inches Minimum And 0.625 Inches Maximum
<b>Head Height:</b>	0.112 Inches Minimum And 0.125 Inches Maximum
<b>Grip Diameter:</b>	0.4360 Inches Minimum And 0.4370 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>Nominal Thread Diameter:</b>	0.438 Inches
<b>Grip Length:</b>	2.428 Inches Minimum And 2.448 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	220000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Special Features:</b>	Conical Bearing Surface Of Head 99.0 Degree To 101.0 Degree Included Angle 0.077 In. Long
<b>Material:</b>	Steel Comp H11 Overall
<b>Material Document And Classification:</b>	Ams 6487 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Nas 672 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/C9535-7-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.