

## P/N CA18091-0HS

## **Description**

Diameter: 23/64", steel comp

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: CA180910HS

Minimum Qty (MOQ):

NSN: 5325-01-030-7016

Schedule B: 7318.15.2010

ECCN: 9A991

National Motor Freight: 066440, Fasteners Curtain / Snap Metal









<sup>\*</sup> See page 2 for technical characteristics

# **P/N CA18091-0HS Specifications**

Grip Length:	0.093 Inches Minimum And 0.150 Inches Maximum
Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Securing Device Type:	Washer
Turnlock Stud Shank Style:	Stud Shank
Extension Length:	0.210 Inches Nominal
Turnlock Stud Head Style:	Fillister
Drive Type:	Socket
Stud Thread Size And Series/type Designator:	0.164-32 Unc
Stud Shank Major Diameter:	0.2470 Inches Minimum And 0.2495 Inches Maximum
Material:	Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	66 Fed Std 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall Or Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

### **How to Order**

Order this captive fastener from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+receptacles/CA18091-0HS">https://military-fasteners.com/studs/turnlock+fastener+receptacles/CA18091-0HS</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://energy.new.order.">https://energy.new.order</a>.