

**Description**

Diameter: 23/64", steel comp

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CA180910HS
Minimum Qty (MOQ):	1
NSN:	5325-01-030-7016
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N CA18091-0HS Specifications

<b>Grip Length:</b>	0.093 Inches Minimum And 0.150 Inches Maximum
<b>Diameter:</b>	0.357 Inches Minimum And 0.373 Inches Maximum
<b>Securing Device Type:</b>	Washer
<b>Turnlock Stud Shank Style:</b>	Stud Shank
<b>Extension Length:</b>	0.210 Inches Nominal
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Drive Type:</b>	Socket
<b>Stud Thread Size And Series/type Designator:</b>	0.164-32 Unc
<b>Stud Shank Major Diameter:</b>	0.2470 Inches Minimum And 0.2495 Inches Maximum
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	66 Fed Std 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this captive fastener from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/CA18091-0HS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.